SEP 1 9 2006

DOCKET NO. IS01350AP



FAX TRANSMITTAL SHEET

Motorola, Inc.

1303 East Algonquin Road

JL01/3rd Floor

Schaumburg, IL 60196

Telephone: Facsimile:

847-862-0270

847-862-8308

18 Number of Pages (including this page)

Date:

September 19, 2006

To:

Jermie E. Cozart - 3726

Location:

United States Patent and Trademark Office

Fax No.:

571-273-8300

From:

Gary J. Cunningham - 33,488

Subject:

10/702,346- Bratek, et al.

Confirmation No.: 8107

NOTICE: This facsimile transmission may contain information that is confidential, privileged, or exempt from disclosure under applicable law. It is intended only for the person to whom it is addressed. Unauthorized use, disclosure, copying or distribution may expose you to legal liability. If you have received this transmission in error, please immediately notify us by telephone (collect) to arrange for return of the documents received and any copies made. Thank you.

MESSAGE:

Enclosed herewith, please find an APPEAL BRIEF for filing in the above-identified application.

RECEIVED CENTRAL FAX CENTER

SEP 1 9 2006

	Application Number	10/702,346							
	Filing Date	November 6, 2003							
TRANSMITTAL	First Named Inventor	Bratek, Daniel J.							
FORM	Group Art Unit	3726							
(to be used for all correspondence after initial filing)		Jermie E. Cozart							
Total Number of Pages in this Submission	Attorney Docket Number 1	IS01350AP							
ENCLOSURES (check all that apply)									
Fee Transmittal Form	Drawing(s)		owance Communication to a						
Fee Attached	Licensing-Related papers	Technology Center (TC) Appeal Communication to Board of Appeals and Interferences							
Amendment/Reply	Petition	X Appeal Communication to TC (Appeal Notice, Brief, Reply Brief)							
After Final	Petition to Convert to a Provisional Application	Proprietary Information							
Affidavits/Declaration(s)	Power of Attorney, Revocation,								
Extension of Time Request	Change of Correspondence Ad		closure(s) (please identify below)						
Express Abandonment Request	Terminal Disclaimer	Terminal Disclaimer							
Information Disclosure Statement	Request for Refund	Request for Refund							
Certified Copy of Priority Documen	S CD, Number of CDs	CD, Number of CDs							
Response to Missing Parts/	Remarks								
Incomplete Application	X Facsimile Transmittal								
Response to Missing Parts									
Under 37 CFR 1.52 or 1.53 SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT									
Firm or	THE OF APPLICANT, ATTORNE	ET, OR AGENT							
Individual Gary J. Cunningh	am 	Registration No.	33,488						
Signature Lang J. Cumning Com									
Date September 19, 2008	7	· · · · · · · · · · · · · · · · · · ·							
	RTIFICATE OF TRANSMISSION								
I hereby certify that this corresponde	nce is being facsimile transmitted	d to the USPTO to fac	simile number						
571-273-8300 or deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, Alexandria, VA 22313 on the date listed below:									
Typed or printed name Tammy Olson									
(0100									
Signature	my Close	Date	September 19, 2006						

RECEIVED CENTRAL FAX CENTER

SEP 1 9 2006

Ø 003/018

UNITED STATES PATENT AND TRADEMARK OFFICE BEFORE THE BOARD OF PATENT APPEALS AND INTERFERENCES

APPLICANT(S)

DAVID J. BRATEK

GROUP ART

3726

UNIT:

APPLN. NO.:

10/702,346

EXAMINER COZART, JERMIE

FILED:

November 6, 2003

Confirmation No.

8107

TITLE:

HIGH PRESSURE SENSOR WITH KNURL PRESS-FIT ASSEMBLY

Date of deposit; September 19, 2006

I bereby certify that this paper is being facsimile transmitted or deposited with the United States Postal Service on the date indicated above, as first-class mail, with sufficient postage attached thereto, in an envelope addressed to Mail Stop Non-Fee Amendment, Assistant Commissioner for Patents, Alexandria, VA 22313 or facsimile transmitted to 571,273.8300.

Signature of Person Mailing P

Tammy Olson

Printed Name of Person Mailing Paper

APPEAL BRIEF

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Sir:

This is Appellants' Appeal Brief.

September 19, 2006 Case No.: IS01350AP (6500/15) Serial No.: 10/702,346 Filed: November 6, 2003

Page 2 of 16

TABLE OF CONTENTS

1.	Real Party In Interest .		•			3
2.	Related Appeals And Interfer	ences			•	4
3.	Status Of Claims .	•		•	,	5
4.	Status Of Amendments			••		6
5.	Summary Of Claimed Subject	t Matt	er.		-	7
6.	Grounds Of Rejection To Be	Revie	wed On	Appcal		8
7.	Arguments		•		•	9
8.	Summary		•	•		12
9.	Claims Appendix .		•		•	13
10.	Evidence Appendix .		•			16
11.	Related Proceedings Append	ix				16

Serial No.: 10/702,346 Filed: November 6, 2003

Page 3 of 16

1. REAL PARTY IN INTEREST

This application is subject to an agreement assigning all rights, title & interest to Temic Automotive of North America, Inc. a subsidiary of Continental A.G., although no such assignment has been recorded to date.

Ø 006/018

September 19, 2006 Case No.: IS01350AP (6500/15)

Scrial No.: 10/702,346 Filed: November 6, 2003

Page 4 of 16

2. RELATED APPEALS AND INTERFERENCES

Appellants and the undersigned attorneys are not aware of any appeals or any interferences which will directly affect or be directly affected by or having a bearing on the Board's decision in the pending appeal.

Serial No.: 10/702,346 Filed: November 6, 2003

Page 5 of 16

3. STATUS OF CLAIMS

Claims 1-12 stand rejected and claims 13-16 were previously withdrawn based on a restriction requirement.

Claims 1-12 stand rejected as unpatentable under 35 U.S.C. §103(a) over Pepperling, 6,715,360 in view of Ito, 5,158,390.

Claims 1-12 are the claims on appeal. See, Appendix.

Serial No.: 10/702,346 Filed: November 6, 2003

Page 6 of 16

4. STATUS OF AMENDMENTS

All amendments to the claims have been entered. Appellants' amendments to the specification have also been entered.

September 19, 2006 Case No.: IS01350AP (6500/15) Serial No.: 10/702,346

Filed: November 6, 2003 Page 7 of 16

5. SUMMARY OF CLAIMED SUBJECT MATTER

In this summary of claimed subject matter, all citations are to the specification of United States Patent Application 10/702,346 filed on November 6, 2003. Further, all citations are illustrative only and support for the cited element may be found elsewhere in the specification.

Independent Claim 1:

One aspect of the invention provides a method of assembling a high pressure sensor with a knurl press-fit for use in an automotive environment. The method includes providing (30) a pressure port 10 having a material with a first hardness and a housing 12 having a material with a second hardness less than the first hardness, the pressure port 10 having a mounting boss and the housing having a receptacle for receiving the mounting boss 14 and configuring (32) the mounting boss of the pressure port with knurls 16 thereon, the knurls 16 oriented parallel to an axis of the pressure port 10. In addition, the method includes pressing (34) the mounting boss 14 of the pressure port 10 into the receptacle 18 of the housing 12 along a direction of the axis such that the knurls 16 deform the receptacle 18 of the housing to conform about the knurls 16 to define a semi-rigid mount. See, e.g. FIG. 3 and pages 7-8 of the specification.

Independent Claim 8:

One aspect of the invention provides a method of assembling a high pressure sensor with a straight knurl press-fit for use in an automotive environment. The method includes providing (30) a pressure port 10 having a material with a first hardness and a housing 12 having a material with a second hardness less than the first hardness, the pressure port 10 having a mounting boss 14 and the housing 12 having a receptacle 18 for receiving the mounting boss 14. In addition, the method includes configuring (32) the mounting boss 14 of the pressure port 10 with straight knurls 16 thereon, the straight knurls 16 oriented parallel to an axis of the pressure port 10, the mounting boss 14 also configured with a shoulder 20 at a first end of the straight knurls 16 and pressing (34) the mounting boss 14 of the pressure port 10 into the receptacle 18 of the housing 12 along an axial direction of the pressure port 10 up to the shoulder 20 such that the straight knurls 16 deform the receptacle 18 of the housing 12 to conform about the straight knurls 16 to define a semi-rigid mount.

September 19, 2006 Case No.: IS01350AP (6500/15) Serial No.: 10/702,346

Filed: November 6, 2003 Page 8 of 16

GROUNDS OF REJECTION TO BE REVIEWED ON APPEAL
Claims 1-12 stand rejected as unpatentable under 35 U.S.C. §103(a) over
Pepperling, 6,715,360 in view of Ito, 5,158,390.

Scrial No.: 10/702,346 Filed: November 6, 2003 Page 9 of 16

7. ARGUMENTS

The §103(a) rejection of claims 1-12 is traversed.

Claims 1-12 stand rejected as unpatentable under 35 U.S.C. §103(a) over Pepperling, 6,715,360 in view of Ito, 5,158,390.

To establish a prima facie case of obviousness, three basic criteria must be met. First, there must be some suggestion or motivation, either in the references themselves or in the knowledge generally available to one of ordinary skill in the art, to modify the reference or to combine reference teachings. Second, there must be a reasonable expectation of success. Finally, the prior art reference (or references when combined) must teach or suggest all the claim limitations. The teaching or suggestion to make the claimed combination and the reasonable expectation of success must both be found in the prior art, not in applicant's disclosure. In re Vaeck, 947 F.2d 488, 20 USPQ2d 1438 (Fed. Cir. 1991). See, e.g. MPEP § 2143. Although a prior art device "may be capable of being modified to run the way the apparatus is claimed, there must be a suggestion or motivation in the reference to do so." 916 F.2d at 682, 16 USPQ2d at 1432.). See also In re Fritch, 972 F.2d 1260, 23 USPQ2d 1780 (Fed. Cir. 1992) (flexible landscape edging device which is conformable to a ground surface of varying slope not suggested by combination of prior art references).

The mere fact that references can be combined or modified does not render the resultant combination obvious unless the prior art also suggests the desirability of the combination. In re Mills, 916 F.2d 680, 16 USPQ2d 1430 (Fed. Cir. 1990) (Claims were directed to an apparatus for producing an aerated cementitious composition by drawing air into the cementitious composition by driving the output pump at a capacity greater than the feed rate. The prior art reference taught that the feed means can be run at a variable speed, however the court found that this does not require that the output pump be run at the claimed speed so that air is drawn into the mixing chamber and is entrained in the ingredients during operation).

It is respectfully submitted that in this matter, there can be no motivation to combine the references. First, Pepperling does not disclose that its method of joining the housing and sensor is anything less than optimal. Therefore, one of ordinary skill in the

September 19, 2006 Case No.: IS01350AP (6500/15) Serial No.: 10/702,346 Filed: November 6, 2003

Page 10 of 16

art would not be motivated to go looking for a better solution, regardless of whether such a solution is provided by Ito. Pepperling discloses that the sensor should be threaded or pressed into the housing (col. 3, lines 7-15), but does not indicate any defects with such attachment, or allege any disadvantage of such attachment. Thus, there can be no reason why one of ordinary skill in the art would be motivated to make any modifications to the Pepperling sensor.

This fact is further augmented by the fact that Ito does not allege that its jointing structure of rotor and shaft is an optimal method of supporting a pressure sensor within a housing. Indeed, the Examiner provides no evidence that those concerned with problems facing pressure sensor designers would consult rotor design references.

In fact, those of skill in the pressure sensor field would note that joints between a rotor and a shaft undergo torque forces as illustrated in Ito, FIGS 7 and 9. Such forces are quite dissimilar to the lateral forces that act on the claimed pressure sensor, as noted on page 5 of the specification. The Examiner provides no facts or evidence that a person of ordinary skill in the art would look to solutions for torquing forces when considering design problems for a part subjected to lateral forces.

Further, the modification suggested by the Examienr would render the prior art unsatisfactory for its intended purpose. If proposed modification would render the prior art invention being modified unsatisfactory for its intended purpose, then there is no suggestion or motivation to make the proposed modification. In re Gordon, 733 F.2d 900, 221 USPO 1125 (Fed. Cir. 1984) (Claimed device was a blood filter assembly for use during medical procedures wherein both the inlet and outlet for the blood were located at the bottom end of the filter assembly, and wherein a gas vent was present at the top of the filter assembly. The prior art reference taught a liquid strainer for removing dirt and water from gasoline and other light oils wherein the inlet and outlet were at the top of the device, and wherein a pet-cock (stopcock) was located at the bottom of the device for periodically removing the collected dirt and water. The reference further taught that the separation is assisted by gravity. The Board concluded the claims were prima facie obvious, reasoning that it would have been obvious to turn the reference device upside down. The court reversed, finding that if the prior art device was turned upside down it would be inoperable for its intended purpose because the gasoline to be filtered would be trapped at the top, the water and heavier oils sought to be separated

Serial No.: 10/702,346 Filed: November 6, 2003 Page 11 of 16

would flow out of the outlet instead of the purified gasoline, and the screen would become clogged.).

In this case, and as noted by the specification, the sensor assembly must be able to "allow[s] some lateral movement to prevent mounting stress sensor error." See, specification, page 3, lines 15-19. In contrast, the Ito reference aims to produce a jointing structure in which a rotor and a shaft are *firmly* jointed. See, col. 1, lines 12-17, inter alia. Rather than firmly jointing the pressure sensor and housing, the instant claims attempt to actually allow some lateral movement. Were a rigid or firmly jointed attachment used, mounting stress sensor error could be introduced to pressure readings from such a sensor – destroying the purpose of the sensor. Since the combined structure would not function as intended, there cannot be any motivation to combine these references.

Therefore, Appellants respectfully request the withdrawal of the rejections to claims 1-12.

Serial No.: 10/702,346 Filed: November 6, 2003

Page 12 of 16

SUMMARY

The Appellants respectfully submit that claims 1-12 fully satisfy the requirements of 35 U.S.C. §§102, 103 and 112. In view of the foregoing, favorable consideration and early passage to issue of the present application is respectfully requested.

Dated: September 19, 2006

Respectfully submitted, Daniel J. Bratek

GARY J.CUNNINGHAM Registration No. (33,488) Attorney for Appellants

Ø 015/018

September 19, 2006

Case No.: IS01350AP (6500/15) Serial No.: 10/702,346

> Filed: November 6, 2003 Page 13 of 16

10. APPENDIX

 A method of assembling a high pressure sensor with a knurl press-fit for use in an automotive environment, the method comprising the steps of:

providing a pressure port having a material with a first hardness and a housing having a material with a second hardness less than the first hardness, the pressure port having a mounting boss and the housing having a receptacle for receiving the mounting boss;

configuring the mounting boss of the pressure port with knurls thereon, the knurls oriented parallel to an axis of the pressure port; and

pressing the mounting boss of the pressure port into the receptacle of the housing along a direction of the axis such that the knurls deform the receptacle of the housing to conform about the knurls to define a semi-rigid mount.

- 2. The method of claim 1, wherein the configuring step includes configuring a shoulder on the mounting boss, and wherein the pressing step include pressing the mounting boss into the receptacle of the housing up to the shoulder.
- The method of claim 1, wherein the providing step includes providing a stainless steel pressure port and an aluminum housing.
- 4. The method of claim 1, wherein the providing step includes providing a length of the knurls that is less than a depth of the receptacle.

Ø 016/018

September 19, 2006 Case No.: IS01350AP (6500/15)

> Serial No.: 10/702,346 Filed: November 6, 2003

Page 14 of 16

- 5. The method of claim 1, wherein the configuring step includes configuring the knurls of the mounting boss and the receptacle to have an interference fit.
- 6. The method of claim 1, wherein the configuring step includes configuring the mounting boss with straight knurls.
- 7. The method of claim 1, further comprising the step of applying a seal to the press fit area to seal the pressure port.
- 8. A method of assembling a high pressure sensor with a straight knurl press-fit for use in an automotive environment, the method comprising the steps of:

providing a pressure port having a material with a first hardness and a housing having a material with a second hardness less than the first hardness, the pressure port having a mounting boss and the housing having a receptacle for receiving the mounting boss;

configuring the mounting boss of the pressure port with straight knurls thereon, the straight knurls oriented parallel to an axis of the pressure port, the mounting boss also configured with a shoulder at a first end of the straight knurls; and

pressing the mounting boss of the pressure port into the receptacle of the housing along an axial direction of the pressure port up to the shoulder such that the straight knurls deform the receptacle of the housing to conform about the straight knurls to define a semi-rigid mount.

017/018

September 19, 2006 Case No.: ISO1350AP (6500/15)

Serial No.: 10/702,346 Filed: November 6, 2003

Page 15 of 16

- 9. The method of claim 8, wherein the configuring step includes configuring the straight knurls to have bevel on an end thereof.
- 10. The method of claim 8, wherein the providing step includes providing a hardened stainless steel pressure port and an aluminum housing.
- 11. The method of claim 8, wherein the configuring step includes configuring the straight knurls of the mounting boss and the receptacle to have an interference fit, and wherein a length of the straight knurls is less than a depth of the receptacle.
- 12. The method of claim 8, further comprising the step of applying a silicone glue to the press fit area to seal the pressure port.

Ø018/018

September 19, 2006 Case No.: IS01350AP (6500/15)

Serial No.: 10/702,346 Filed: November 6, 2003

Page 16 of 16

Evidence Appendix

None

Related Proceedings Appendix

None.